

foot-operated IMPULSE SEALERS

Foot-operated impulse sealers are ideal for high volume poly bag & other thermoplastic sealing. The sealers are capable of sealing 15-20 bags per minute. These sealers allow you to keep both hands free for quicker and more accurate sealing. The machines are also equipped with a plug-in timer. The timer controls the sealing time needed for different materials. Once the timer is set, it will give a consistently flat seal. When seal is done, the sealer will automatically beep or the signal light on timer will turn off.

TISF Series are light blue in color and are available in 12", 18", & 24" with a 2mm or 5mm seal width. Depending on the model of the sealer, materials up to 24" wide and with 16 mil total thickness can be sealed. Holes have been pre-drilled for imprinter attachment. The sealers include a 26" pedestal, a 2" base, an adjustable worktable, & an adjustable foot control. An optional 36" pedestal for standing operation is available. The manufacturer's replacement kit includes 2 elements and 1 fuse.

Easy to operate: Set the timer, insert the bag between the sealing bars, press down the foot board & release after timer goes off. To enhance the appearance of the seal, hold down the foot board for an additional 1 to 2 seconds after the timer light goes off.



Size	Seal Width	Model#	Watts	Wt. (lbs.)
12"	2mm	TISF-302	400w	55
18"	2mm	TISF-452	600w	65
24"	2mm	TISF-602	800w	68
12"	5mm	TISF-305	600w	62
18"	5mm	TISF-455	900w	68
24"	5mm	TISF-605	1200w	71

*ROUND WIRE HEATING ELEMENTS are available for cut & seal applications at no additional cost. When ordering, add the letters "rnd" to the model number# - i.e. TISF-302rnd.

IT-863/RS-8

A 3-Line mountable imprinter is an available option. It mounts on the upper jaw of the sealer. Seal and print in one single operation. Ribbon colors available in black, blue, white, red, & gold.

MFG 02.12.09. EXP 0 0.12.09. LOT 7 3 5 B Q D

Printing Sample (actual size)

